




DESCRIPTION

Downhill Dan 35 is a quick-to-install, recessed down-lighter profile. The asymmetric mounting bracket makes this product unique and means that it can be installed with the LED strip already attached. Downhill Dan 35 has plenty of power for a huge range of applications. Silver anodised or white powder coat are standard finish options.

FEATURES

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- PMMA diffuser - scratch and mark resistant
- Max. 30 W per metre

TECHNICAL DATA

APPLICATIONS	General downlighting in kitchens, living rooms, dining rooms, reception counters, lobbies
INSTALLATION	Interior Exterior (with IP65 LED strip)
MOUNTING	Recessed
MATERIALS	Extruded aluminium body PMMA diffuser Aluminium end caps
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details
LIGHT SOURCE	LED ribbon strip
SDCM*	2-step MacAdam
CRI*	≥ 95
R9*	80+
SOURCE LIFE*	L80 B10=82 000 hrs
FINISH	   Custom colours available

* Figures for the PRO Series LED Strips



LED STRIP

PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
314 lm	314 lm	338 lm	652 lm	652 lm	700 lm	966 lm	1026 lm	1038 lm	1570 lm	1594 lm	1618 lm

RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
63 lm	167 lm	41 lm	242 lm

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%

ACCESSORIES



JN-ST-23
Straight joiner



JN-90-23
90 degree joiner



MB-DD35
Mounting bracket



SMRB
Seismic restraint
bracket

